

SBC Western Red Cedar Shingle Program

*The Inspiring beauty of wood
with the uncompromising quality of SBC*



SBC

PRE-STAINED OPTIONS

SBC offers all grades of KD and pre-stained 18" western red cedar shingles, including Perfections, Resquared and Rebutted (R&R) and 5/8" Tapersawn Premium.

FINISHES	TYPE OF STAIN	NO OF COATS	WARRANTY ON STAIN ^c FOR SIDEWALL APPLICATION ONLY
Primed (clear or white/gray)	Oil / Latex (low VOC)	1	2 years (need to be topcoat within 60 days)
Bleaching Oil / Weathering Stain	Oil	1	No finish warranty - Aging products
Naturaltone Cedar (Olympic Maximum)	Oil	1	3 years against graying
Semi-transparent (Olympic colors) ^B	Latex (low VOC)	1	5 years against peeling and flacking
Solid colors (any colors) ^{A&B}	Latex (low VOC)	2 or 3	10 / 25 years against peeling and flacking

A : For best results, our solid color option include 1 coat of the PPG Seal Grip™ blocking primer (latex). This product provides maximum tannin stain inhibition.
 B : PPG Machinecoat™ 100% acrylic stain are low VOC. They are also mildew resistant, water-repellent and UV resistant.
 C : Failure to follow Cedar Shake and Shingle Bureau's installation manual will void the warranties. Some restrictions apply. See detailed warranties.

SPECIFICATIONS

PRODUCTS	DESCRIPTION	LENGHT & THICKNESS	AVAILABILITY
Perfections	Regular Shingles	18" x 7/16"	KD and pre-stained
Resquared and Rebutted (R&R)	Trimmed for paralled edges with butts sawn at right angle For faster installation and uniform appearance	18" x 7/16"	KD and pre-stained
Tapersawn	Sawn on both sides Thicker shadow line Tailored smooth style	18" x 5/8"	KD and pre-stained (Weathering stained / Bleaching oil only)

In stock at SBC: Perfections No 1, Resquared and Rebutted (R&R) No 1 and Tapersawn Premium.
 All these grades are 100% heartwood, 100% clear and 100% edge grain. Other grades available on special orders.

BUNDLING / COVERAGE CHART

APPROX COVERAGE PER BUNDLE/BOX (in sq. ft.) at indicated weather exposures	PERFECTIONS	RESQUARED & REBUTTED (R&R)	TAPERSAWN
5"	22	36	15
5 1/2"	25	39	16
6"	27	43	17
6 1/2"	29	46	18
7"	32	50	19
7 1/2"	34	53	20
Recommended exposure (Roofs / Walls)	5" / 6"	5" / 6"	5" / 6"
Boxes per square	4	2	5
Boxes per unit	40	30	50

For installation and technical details, visit www.cedarbureau.org or bcshakeshingle.com

Note : These specifications can vary. Use them simply as a guide.