

# Stunning and sophisticated

Whether you choose Thermory Benchmark Ash for decking, cladding, or porch flooring, this gorgeous hardwood sets the bar for longevity and stability with proven rot resistance and a timeless aesthetic. Plus, our thermal modification process delivers consistency across every board for easy installation and impeccable construction.



**SPECIES:**

White ash

**APPLICATIONS:**

Decking  
Cladding  
Porch flooring



Thermally modified



Sustainable



Weather resistant



Lightweight material



Smooth cutting



Rot resistant





## Decking

Create your dream outdoor space with durable, hardwood decking

<b>WIDTHS:</b>	3.5" - 7.5"
<b>THICKNESSES:</b>	0.79" - 1.65"
<b>INSTALLATION TYPES:</b>	VISIBLE, HIDDEN, PACS



## Cladding

Give your walls a lift by bringing out their natural charm

<b>WIDTHS:</b>	3.5" - 7.5"
<b>THICKNESSES:</b>	0.79" - 1.65"
<b>INSTALLATION TYPES:</b>	VISIBLE, HIDDEN, SCREW



## Porch flooring

Relax on a porch built for lazy days and quiet nights

<b>WIDTH:</b>	3.5"
<b>THICKNESS:</b>	0.79"
<b>INSTALLATION TYPE:</b>	VISIBLE, HIDDEN

## Color transformation

Wood's natural aging process is influenced by how much exposure it has to the elements. The more Benchmark Ash is exposed to UV light and rain, the faster its color will transform from brown to silver—sometimes in as little as six months. To maintain your wood's natural color outdoors, simply treat the boards with a penetrating UV protective oil.



**THERMORY**<sup>®</sup>  
LEAVE A LASTING IMPACT

Phone: 585-591-6590  
Email: [support@thermoryusa.com](mailto:support@thermoryusa.com)

→ [ThermoryUSA.com](https://www.thermoryusa.com)

