

THE SBC ADVANTAGES



TRUEST R&R SHINGLES ON THE MARKET

R&R precision 1/64" up to 10" from the butt



REVERSIBLE SHINGLES

Graded on both sides



DURABLE FINISH

Exclusive factory-finished dipping process putting more stain below the 5" exposure line



15% WIDER THAN **INDUSTRY STANDARD**

A minimum width of 3-7/16



OPTIMAL WOOD STABILITY

Kiln-dried by dehumidification producing less brittle shingles



VALUABLE TIME-SAVER FEATURES

Embossed nailing line on every shingle, installation tool and touch-up kits





UP TO 3X FASTER!





WHITE CEDAR GRADES



Extra « A »



- Superior quality
- No imperfections

Sidewall Select « AB »



- Wider for faster installation
- · No imperfections on exposed surface

Clear « B »



- · Standard quality
- · No imperfections on exposed surface

2nd Clear « C »



- Economy quality Sound knots, rustic appearance

Calculating the Quantity Required Area Covered by 1 box

•								
Exposures	Area Covered							
4"	20 sq. ft.							
4.5"	22.5 sq. ft.							
5" (standard)	25 sq. ft.							

IN-STOCK PROGRAM

nDc		Extra «A»			Sidewall Select « AB »		Clear « B »			2 nd Clear « C »			Warranty			
PPU			Natural	1 coat	2 coats	Natural	1 coat	2 coats	Natural	1 coat	2 coats	Natural	1 coat	2 coats	Finish	Wood Decay
Solid colors	Buzzards Bay Gray	>/					Х	Х							1 coat = 10 years, including 2 years labor 2 coats = 25 years including 5 years labor	30 years, including 5 years labor
	Cape Cod Gray	//					X	X								
	Concord White	//						X								
	Driftwood Gray	//					Х	Х								
	Green Tea Leaf	//					Х	Х								
	Harbor Gray	//					Х	Х								
	Montauk Sand	//					Х	Х								
	Monterey Gray	//					Х	Х								
	Nantucket Gray	//					Х	Х								
	Safari Beige	//					Х	Х								
	Sandstone	//					x	х								
	Sea Shell	>/					Х	Х								
Naturaltone	Olympic Maximum 57503	>/					Х								NO	30 years, including 5 years labor
Weathering Agents	Enviro Bleach						Х								NO	30 years, including 5 years labor
	Bleaching Oil	>//					Х									
	Weathering Stain	>/					х									
Primer (Must be top-coated within 6 months)	Gray Pro-prime	//					Х									30 years, including 5 years labor
	White Pro-prime	71					Х								NO	
Natural	Green		Х			х			×			Х				NO
	Kiln-Dried (KD)		Х			Х			×			X			NO	